

# ประหยัดงบประมาณ

เครื่องราชการ

หน่วยงานรัฐวิสาหกิจและเอกชน

**SPENDER**<sup>®</sup>  
THE PERFECT TWO WAY RADIOS



รับปรึกษาคณะกรรมการ  
ช่วยเหลือและบริหาร

**COMMERCIAL RADIO FM TRANSCEIVER**  
**199 CHANNELS, 1100 mAh LI-ION BATTERY**  
**50 GROUPS OF CTCSS**  
**214 CODES OF DCS**  
**HIGH/MID/LOW POWER SWITCHABLE**  
**ADJUSTMENT POWER LINEAR SET UP**  
**PC PROGRAMMABLE FREQUENCY**  
**AUTO POWER OFF**  
**PC PROGRAMMABLE**  
**ROGER BEEP SOUND (ROG)**  
**S-METER BAR**  
**VOX SYSTEM**  
**PASSWORD SECURITY PRIVATE**  
**FREQUENCY DISPLAY MODE**  
**CHANNEL DISPLAY MODE**  
**MEMORY DISPLAY MODE**  
**SET UP NAME REPLACE CHANNEL**  
**SELECT WIDE/NARROW-BAND**  
**DUPLEX FUNCTION**  
**SCAN SYSTEM**  
**TIME-OUT-TIMER**  
**ETC.**



**SCRAMBLER**  
DIGITAL CODES  
BATTERY LI-ION.



**DHS 7500**  
FREQ.136-173.9950MHZ

ม็องกันการดักฟัง 100%



**Specification**

**DHS 7500**



**General**

Frequency cover Range	136.0000 - 173.9950MHz
Mode Type	FM (F3E)
Frequency Stability	+/-5 ppm (-20° C to -55° C)
Operating temperature range	-20° C to +55° C
Power supply requirement	7.4 V DC.
Current stand-by	40 mA.
Current transmitting	1200 mA.
Antenna impedance	50 Ohm.
Dimensions	110 x 50 x 30 mm. (w x h x d)
Weight with battery	250 g.
Step frequency	25 KHz/12.5KHz.
Channel spacing	12.5 KHz/25 KHz.



**Transmitter**

Transmitting current drain	Hi <1.5A
Power output	Hi : 5 W. MID 2 W. Lo : 1 W.
Transmitting Frequency error	+/-500Hz.
Spurious radiation	73 dBm.
Adjacent channel power	<-73 dBm.
Max.frequency deviation	+/-3KHz.
Tx distortion	<5 %
Harmonious wave	<70 %
Tx frequency response	+1dB to-3dB of+6dB. Octave with 300~3000 Hz. For 1000Hz. reference PRE/EMP.



**Receiver**

Sensitivity	<0.25 µV at 12 dB. / SINAD
Squelch sensitivity	0.158 µV.
Selectivity	< 70 dBm.
Intermodulation Modulation	70 dB.
Squrious response rejection	70 dB.
Adjacent channel selectivity	70 dB.
Frequency Stability	+/-5 ppm
Audio output	>400 mW.
Rx distortion	< 5% at 8 Ohm Speaker
Rx frequency response	+1dB to-3dB of+6dB. Octave with 300~3000 Hz. For 1000Hz. reference DE/EMP.



Distribution By  
ศูนย์ลูกค้าสัมพันธ์

Helpline on : 0-2392-1500

If you still have any problems, please contact our Customer Cares.

: Monday- Saturday 8.30 am.-5.30 pm.

: Sunday and Public Holidays : Closed

[www.tccom.co.th](http://www.tccom.co.th)



Dealer's Stamp

