

# ความสุขที่หยุดไม่อยู่กับ เทคโนโลยีใหม่สุดฮอต

E2452

0.5  
watts

Li-Ion  
1200mAh

## แรงจัดด้วย

- DIGITAL 214 CODES
- CTCSS 50 CODES
- LI-ION 1200 mAh
- CHANNEL & FREQUENCY DISPLAY
- MEMORY MODE
- RING TONE PRIVATE MELODY
- BACKLIGHT SETTING
- ใช้งาน 12 ชั่วโมง

**BEST QUALITY**

ยกเว้นใบอนุญาตใช้



CHANNEL & FREQUENCY DISPLAY

CTCSS

DCS

VOX

TOT

HI/LO POWER



รับประกันคุณภาพ  
อะไหล่และบริการ

>>>>>

**Specification**

**E2452**

>>>>>

**General**

Frequency cover range	245.0000 - 245.9875MHz
Mode Type	FM (F3E)
Frequency Stability	+/-5 ppm (-20°C to +55°C)
Operating temperature range	-20°C to +55°C
Power supply requirement	3.6 V DC.
Current stand-by	40 mA.
Current transmitting	< 650mA.
Antenna impedance	50 Ohm.
Dimensions	100 x 55 x 27 mm. (h x w x d)
Weight with battery	230 g.
Step frequency	12.5 KHz
Channel spacing	12.5 KHz

>>>>>

**Transmitter**

Power output	Hi : 0.5 W. Lo : 0.2 W.
Transmitting Frequency error	+/-500Hz
Spurious radiation	60 dB.
Adjacent channel power	< -63 dBm.
Harmonious wave	< -63 dBm.
Max frequency deviation	0.300 ~ 2.45KHz / 20 dB up
Tx distortion	< 5 %
Tone frequency output	0.4 - 0.75KHz.
Tx frequency response	+1dB to -3dB of +6dB. Octave with 300~3000 Hz. For 1000Hz. reference PRE/EMP.

>>>>>

**Receiver**

Sensitivity	< -118 dBm. at 12dB/SINAD
Squelch sensitivity	-120 dBm.
Selectivity	< -65 dBm.
Intermodulation Modulation	60 dB.
Squrious response rejection	60 dB.
Adjacent channel selectivity	63 dB.
Frequency Stability	+/-5 ppm
Audio output max	> 200 mW.
Rx distortion	< 5% at 8 Ohm Speaker
Audio frequency response	+1dB to -3dB of +6dB. Octave with 300~3000 Hz. For 1000Hz. reference DE/EMP.

>>>>>

Distribution By  
ศูนย์วิทยุสื่อสาร

**Helpline on : 0-2392-1500**

If you still have any problems, please contact our Customer Cares.

: Monday- Saturday 8.30 am.-5.30 pm.  
: Sunday and Public Holidays : Closed

[www.tccom.co.th](http://www.tccom.co.th)



Dealer's Stamp

